

EXPERIMENTAL DETERMINATION OF HYDROGEN DIFFUSION RATES IN HYDROUS MINERALS USING THE ION MICROPROBE

Suman K. De^{1,2}, David R. Cole¹, Lee R. Riciputi¹, Thomas Chacko², and Juske Horita¹.

¹ Chemical and Analytical Sciences Division, Oak Ridge National Laboratory, Oak Ridge, Tennessee 37831-6110

² Department of Earth and Atmospheric Sciences, University of Alberta, Edmonton, Alberta, Canada T6G 2E3

Accurate determination of hydrogen diffusion rates are necessary to understand the mechanism of hydrogen isotope exchange between hydrous minerals and water, and to interpret H isotopes from natural systems. However, hydrogen diffusion coefficients, knowledge of transport mechanisms of hydrogen, and reaction kinetics between fluids and hydrous phases such as epidote, amphibole, and the micas are poorly determined at present. Hydrogen diffusion rates have been almost entirely determined empirically from bulk powder-fluid exchange experiments, using different grain geometry models to estimate the rates of fast and slow diffusion (Graham, 1981). A better approach is to react deuterated water with hydrous crystals and measure D/H profiles using secondary ion mass spectrometry.

Single crystals of museum-quality epidote and pargasite were mineralogically characterized (e.g., SEM; electron microprobe), cut and polished perpendicular to specific crystallographic axes prior to hydrothermal experimentation. The single crystals were placed in gold capsules with 50 – 100 mg of 99% deuterated water. Experiments were conducted in cold-seal vessels, typically at 2kbar (\pm 25 bars) for durations of 6 hrs to 18 days depending on the temperature. The surface of each reacted crystal was carefully examined both optically and by SEM, for the presence of epitaxial crystal growth or surface roughness resulting from dissolution. Only those crystals that exhibited minimal roughness ($<0.1\mu\text{m}$) and an absence of surface mineral growth were selected for SIMS analysis. The samples were sputtered using a ¹⁶O primary ion beam with an impact energy of 17 keV. Primary beam currents were 25-100 nA with a diameter of 30-60 μm and the beam was rastered over 100x100 to 150x150 μm^2 areas. A field aperture was used to restrict analysis to ions sputtered from the central $\sim 33\mu\text{m}$ diameter of the crater. Crater depths, measured using a profilometer, ranged from 0.2 to several μm .

Two methods have been used for calculating the diffusion coefficients from the ion probe data. In the first approach, self-diffusion of deuterium is modeled as transport into a semi-infinite medium whose surface is maintained at a constant isotopic composition different from that initially in the crystal (Crank, 1975; Gilletti et al., 1978). A second related method uses the Levenberg-Marquardt algorithm, a non-linear least-squares technique (Labotka et al., 2000). Both approaches give essentially the same diffusivities. Using SIMS we are also determining hydrogen diffusivity in phlogopite, muscovite, chlorite and brucite.

We have measured D/H profiles parallel to the *b* crystallographic orientation (faster direction) in epidote reacted with deuterated water between 200 and 600°C at 2 kbar. For example, the range of diffusion coefficients between 200 – 600°C and 2kb for epidote is between the values of $\log D = -13.6$ to $-17 \text{ cm}^2/\text{sec}$. Similarly, we measured the D/H profiles in pargasite (calcic amphibole) reacted with deuterated water at 300 – 400°C and 2 kbar, but parallel to the faster *c* crystallographic direction. The diffusion coefficient at 400°C and 2 kbar for pargasite is $\log D = -15.2 \text{ cm}^2/\text{sec}$. Preliminary activation energies for both of these experimental systems are $\sim 67 \text{ kJ/mol}$. The diffusion coefficients for epidote (200 – 600°C) and pargasite (300 – 400°C) are significantly slower than those estimated from either a plate or cylinder model using the bulk exchange data (Graham, 1981; Graham et al., 1980, 1984). A mixed recrystallization-diffusional process in bulk exchange experiments compared to purely self-diffusion process in single crystals may in part account for the faster rates in the bulk experiments. Additionally, selection of the grain size, grain geometry and diffusion model can have profound influence on the estimates of diffusivity from the powdered experiments. Results obtained with the present single-crystal technique have broad ramifications for the applications of hydrogen isotopes not only in geothermometry, but also in coupling natural isotopic distribution with rate data to quantify the duration of a particular fluid-rock interaction.

References :

Crank J. (1975) *The Mathematics of Diffusion*. 2nd Edition, Oxford University Press, Oxford, England.

Giletti B.J., Semet M.P. and Yund R.A. (1978) *Geochim. Cosmochim. Acta* 42, 45-57.

Graham C.M. (1981) *Contrib. Mineral. Petrol.* 76, 216-228.

Graham C.M., Sheppard S.M.F., and Heaton T.H.E. (1980) *Geochim. Cosmochim. Acta* 44, 353-364.

Graham C.M., Harmon R.S., and Sheppard S.M.F. (1984) *Am. Min.* 69, 128-138.

Labotka, T., Cole, D.R. and Riciputi, L.R. (2000) *Am Min.* 85, 488-494.

*Research sponsored by the Chemical Sciences, Geoscience and Biosciences Research Program, Office of Basic Energy Sciences, U.S. Department of Energy under contract DE-AC05-00OR22725, Oak Ridge National Laboratory, managed and operated by UT-Battelle, LLC.

"The submitted manuscript has been authored by a contractor of the U.S. Government under contract No. DE-AC05-00OR22725. Accordingly, the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for U.S. Government purposes."